

ARC200 PFC



Features:

- Rugged, robust, and industrial look with ergonomic design
- **ClearVision** Technology
- **Intelligent synergic control**
- **Smart Lift TIG**
- Adaptable wide voltage range
- Quick factory reset
- Anti-stick, adjustable Hot Start and Arc Force
- Dedicated wireless remote control (minimalist version)
- Remote control receiver module (optional)
- Power factor correction (PFC), generator-friendly
- **ABAP: Active Balancing Air Passage**
- On demand fan
- Voltage Reduction Device (VRD)
- Key power electronic component protection
- Overcurrent and overheat protection



SISAB
SVETS & VERKTYGSGRÖSSISTEN SINCE 1987

Specifikationer:

		ARC200 PFC Z2S42	
Ingångseffekt		AC95–265 V, 50/60 Hz	
		AC115 V	AC230 V
Öppen kretsspänning		78V	
MMA	Märk ingångsström	31,2 A	29,7 A
	Nominell ineffektkapacitet	3,6 kVA	6,8 kVA
	Utgångsströmsområde	20–120 A	20–200 A
	Nominell arbetscykel	25 %	
TIG	Märk ingångsström	27,2 A	19,6 A
	Nominell ineffektkapacitet	3,1 kVA	4,5 kVA
	Utgångsströmsområde	10–160 A	10–200 A
	Nominell arbetscykel	25 %	
Effektivitet		85 %	
Effektfaktor		0,99	
Tom statsmakt		MMA: 46,8 W TIG: 7 W	
skyddsklass		IP23S	
Isoleringsklass		H	
Mått LxBxH		413x150x311 mm	
Nettovikt		7,2 kg	



Standardtillbehör

- 2 st snabbpluggar

