

TIG200P PFC



Features:


- Rugged, robust, and industrial look with ergonomic design
- **ClearVision** Technology
- Adaptable wide voltage range
- **Dash-Arc**
- **Smart Lift TIG**
- Full-featured pulse TIG parameters
- Flexible remote control solutions
- Power factor correction (PFC), generator-friendly
- Quick factory reset; auto sleep mode
- **ABAP: Active Balancing Air Passage**
- **Smart gas** for optimized shielding gas consumption
- On demand fan
- Voltage Reduction Device (VRD)
- Key power electronic component protection
- Overcurrent and overheat protection



SISAB
SVETS & VERKTYGSGRÖSSISTEN SINCE 1987

Specifikationer:

		TIG200P PFC W2S62	
Ingångseffekt		AC95–265 V, 50/60 Hz	
		AC115 V	AC230 V
Öppen kretsspänning		68 V	
TIG	Märk ingångsström	29,7 A	19,5 A
	Nominell ineffektkapacitet	3,4 kVA	4,5 kVA
	Utgångsströmsområde	5–160 A	5–200 A
	Nominell arbetscykel	25 %	
MMA	Märk ingångsström	31,6 A	25,6 A
	Nominell ineffektkapacitet	3,7 kVA	5,9 kVA
	Utgångsströmsområde	10–120 A	10–180 A
	Nominell arbetscykel	25 %	
Effektivitet		84 %	
Effektfaktor		0,99	
Tom statsmakt		MMA: 33 W TIG: 7 W	
skyddsklass		IP23S	
Isoleringsklass		H	
Mått LxBxH		453x150x313 mm	
Nettovikt		8,97 kg	



Standardtillbehör

- 4M SGT26-S1 180A TIG fackla
- 3M öronklämma
- 1 st snabbuttag
- 2 st slangklämmor
- 1 st snabbplugg
- 1 st volframelektrod

