








Magnetic drill

ECO.40/2



Key specifications

| | | | |
|--|---|---|---|
| Cutters | Twistdrills | Countersink | |
|  |  |  | |
| 40 mm | 13 mm | 45 mm | |
| 1 9/16" | 1/2" | 1 3/4" | |
| Weight | Motor | Magnet | Stroke |
|  |  |  |  |
| 12 kg | 1050 W | 1500 kg | 150 mm |
| 26.5 lbs | 9.5 A | 3300 lbs | 5 15/16" |

Technical data

| | Metric | Imperial |
|------------------|---------------------------|-----------------------|
| Annular cutter | Ø 32 mm | Ø 1 9/16" |
| Twist drill | Ø 13 mm | Ø 1/2" |
| Countersinking | Ø 40 mm | Ø 1 3/4" |
| Length | 320 mm | 12 5/8" |
| Width | 210 mm | 8 1/4" |
| Height | 370 - 512 mm | 15 9/16" - 21 1/4" |
| Stroke | 150 mm | 5 15/16" |
| Weight | 12 kg | 26.5 lbs |
| Magnet (lwxh) | 160x80x42 mm | 6 5/16"x3 1/8"x1 5/8" |
| Magnetic force | 1500 kg | 3300 lbs |
| Motor power | 1000 W | 9.5 A |
| Speed (no load) | 720 min ⁻¹ | 720 rpm |
| | 1300 min ⁻¹ | 1300 rpm |
| Speed (load) | 315 min ⁻¹ | 315 rpm |
| | 560 min ⁻¹ | 560 rpm |
| | (1050W) | (9.5 A) |
| Spindle (Weldon) | 19,05 mm | 3/4" |
| Power supply | 110 - 120 V AC / 50-60 Hz | |
| | 220 - 240 V AC / 50-60 Hz | |

Additional benefits:

- **2-speed gearbox**
- **Compact design**
- **Detachable spindle**
- **Practical long stroke**
- **Clear and easy controls**