







Magnetic drill - low profile

ECO.36

Key specifications

HOOGTE SLECHTS

165 mm / 6 1/2"

Cutters	In-corner	Height
		
36 mm	50 mm	165 mm
1 7/16"	12"	6 1/2"
Weight	Motor	Magnet
		
10.3 kg	1050 W	1200 kg
22.7 lbs	9.6 A	2650 lbs



Technical data

	Metric	Imperial
Annular cutters	Ø 36 mm	1 7/16"
Countersink	Ø 40 mm	1 9/16"
In-corner drilling	0°: 50 mm	2"
	90°: 53 mm	2 1/16"
	45°: 60 mm	2 3/8"
Length	310 mm	12 3/16"
Width	135 mm	5 5/16"
Height	165 mm	6 1/2"
Stroke	40 mm	1 9/16"
Weight	10.3 kg	22.7 lbs
Magnet (lxwxh)	80x160 mm	3 1/8"x6 5/16"
Magnetic force	1200 kg	2645 lbs
Motor power	1050 W	9.6 A
Speed (no load)	700 min ⁻¹	700 rpm
Speed (load)	400 min ⁻¹	400 rpm
	(1050 W)	(9.6 A)
Spindle (Weldon)	19,05 mm	3/4"
Power supply	110 - 120 V AC / 50-60 Hz	
	220 - 240 V AC / 50-60 Hz	

Additional benefits:

- User-friendly quick-connect cutter fitment system
- Detachable ratchet feed handle for left and right use
- Removeable and slidable up and down safety guard
- Integrated motor cable
- Safety strap attachment integrated

